


Schottky Barrier Diode



Features

- Moisture sensitivity level 1
- Reverse voltage: 40V
- Average forward current: 1A

Application

- Fast switching speed
- For general purpose switching applications

Mechanical data

- **Package:** DFN1608-2L
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Device marking code			R
Repetitive peak reverse voltage	V_{RRM}	V	40
Forward current	I_F	A	1
Repetitive peak forward current @ $t_p \leq 1 \text{ ms}; \delta \leq 0.25$	I_{FRM}	A	3
Non-Repetitive Surge peak forward current @ $t=8.3\text{ms}$ half-sine wave	I_{FSM}	A	5
Power Dissipation	P_D	mW	410
Junction temperature	T_J	$^\circ\text{C}$	-55 to +125
Storage temperature	T_{STG}	$^\circ\text{C}$	-55 to +150



MBR1040THG

RoHS
COMPLIANT

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Typ	Max
Reverse voltage	V _R	V	I _R =10uA	40		
Forward Voltage	V _F	mV	I _F =100mA			390
			I _F =500mA			500
			I _F =700mA			550
			I _F =1A			600
Reverse Leakage Current	I _R	uA	V _R =10V			4
			V _R =40V			20
Capacitance	C	pF	V _R =1V,f=1MHz			60
			V _R =10V,f=1MHz			25
Reverse Recovery Time	T _{rr}	ns	I _F =I _R =0.5A, I _{rr} =0.1A		15	25

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	245
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	200

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint



■ Characteristics

Fig 1: P_D-T_a Curve




Fig 2: Capacitance Capability




Fig 3: Typical Forward Characteristics





Fig 4: Typical Reverse Characteristics






MBR1040THG

RoHS
COMPLIANT


Ordering Information

Preferred P/N	Packing Code	Unit Weight(g)	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MBR1040THG	F1	Approximate 0.0026	3000	30000	120000	Tape & Reel

Outline Dimensions



Suggested Pad Layout



UNIT: mm



MBR1040THG

RoHS
COMPLIANT

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.